

PRODUCT INFORMATION

FT101™ Conditioner



DESCRIPTION

FT 101™ Conditioner is a buffered acid used to etch and profile concrete prior to the application of thin mil products. Helps to prevent acid fumes from damaging machinery or roller conveyers, thereby protecting equipment from damage and repair or replacement costs.

ADVANTAGES

- User friendly
- May be sprayed
- Water soluble
- Ease of removal

PACKAGING

Available in five (5) and 55-gallon drums.

COVERAGE

FT 101™ Conditioner is applied via a low pressure sprayer at an approximate rate of 100 sq ft per mixed gallon.

MIXING RATIO

1 part FT 101™ to 5 parts water

LIQUID MATERIAL PROPERTIES

Property	Test Method	Results
Acids Used	NA	Hydroxyacetic Acid Hydrochloric Acid
Solvents	NA	Carbitol Acetate
Percent Actives		53
Flash Point, °F (°C) Seta Closed Cup	ASTM D3278	>200 (93)
Density, lb/gal (kg)	ASTM D1475	9.54 (1.15)
pH @ 1%		1.5 - 2.5
Color		Orange
Odor		Acidic
Percent Biodegradable		100
Application Characteristics	Use Level	Approx. 1 gal / 100 sq ft

Charlotte 13732 Statesville Road Huntersville, NC 28078 (800) 955-0078 (704) 948-5535 Fax (704) 948-7552

Tampa 7824-A Causeway Blvd. Tampa, FL 33619 (800) 390-7727 (813) 635-0004 Fax (813) 635-0244

Atlanta Industrial Floor Coating 3375 Hutchinson Road B-1 Cumming, GA 30040 (800) 955-1580 (770) 844-0552 Fax (770) 844-0553

www.floortechinc.com